

# Automatic Syringe Assembly Machine With Oil Injection

(Normal Speed Model I, High Speed Model II)



## Advantages

- Fast speed with high conformity rate
- Low noise, no pollution for products and clean room
- Steady work continuously for 24 hours
- Intelligent auto-pause and auto-restart
- Simple operation with one operator only
- With safety to auto-pause immediately when it is open
- Stainless Steel (SUS304) is used when components are exposed to products.
- MC(Nylon) is produced by special food conveyor belt of FDA certified manufacturer.
- Anti-corrosion treatment

### Application

- Luer slip
- Luer lock
- Eccentric luer tip
- With or without needle mounted.

### Key Components and Brands

Mainframe Reducer	Solenoid Valve	Photoelectric Switch	Steel of Feeder
Wenlin Enwei	Shako	SICK	Nanjing Tuohai
PLC	Touch Panel	Frequency Converter	Mainframe Motor
Mitsubishi	Mitsubishi	Mitsubishi	Wenlin Enwei

### Technical Specifications

Operator	Rated Volt	Power	Rated Air Pressure	Equipment Size	weight
1 person	AC220V/50hz	3KW	0.4-0.6MPa	4650*2630*2150mm	Model I 1550kg
					Model II 1500kg

(Normal Speed Model I, High Speed Model II)

### Production Efficiency (pcs/min)

Model	1ml/2ml	3ml/5ml	10ml/20ml	30ml	50ml/60ml
Normal Speed I	160-180	200-220	180-200	160-180	140-160
Fast Speed II	300-330	300-320	260-280/240-260	180-200	

(Normal Speed Model I, High Speed Model II)